

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 02102663.8
Demande no:

Anmeldetag:
Date of filing: 28.11.02
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

WHIRLPOOL CORPORATION
2000 M-63
Benton Harbor
Michigan 49022
ETATS-UNIS D'AMERIQUE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se referer à la description.)

Dishwasher

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

A47L15/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR



**Eur päisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02102663.8

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)

directed jet presents a percentage of open area lower than the percentage of open area of the remaining portions of the filter.

Thanks to such technical feature, air suction toward the circulating pump is avoided so that a smooth pump operation is assured (high pump stability). Since air is no longer brought to the pump suction area, the water level can be lowered, which means lower water amount per fill.

According to a first embodiment of the invention, in which the filter is a perforated or punched metal plate, for instance made of stainless steel, such filter presents one central zone and two side zones outside the circular pattern of the downwardly directed jet, such side zones having a plurality of holes with a pitch (distance between the centres of holes or perforation) smaller than the pitch of holes in the central zone.

According to a second embodiment of the invention, in which the filter is made of polymeric material, such filter presents a substantially circular zone, corresponding to the circular pattern of the downwardly directed jet, with no hole or perforation.

The invention will be further described by way of non-limiting example with reference to the accompanying drawing in which:

- Figure 1 is a perspective view of a dishwasher according to the invention;
- Figure 2 is a section along line II-II of figure 1,
- Figure 3 is a plan view of the fine-mesh filter used in the dishwasher of figures 1 and 2 according to a first embodiment of the invention,
- Figure 4 is a plan view of the fine-mesh filter used in the dishwasher of figures 1 and 2 according to a second embodiment of the invention,
- Figures 5 and 6 are enlarged views of different portions of figure 3.

Referring to figure 1, a dishwasher 10 comprises a washing tank 12 provided with a front opening 14 which can be closed by a pivoting door 16. The washing tank 12 is provided at the bottom thereof with a chamber 18 (figure 2) for collecting the washing and rinsing water. Disposed in the chamber 18 is a circulating pump 20 which is capable of feeding at least one rotary arm 22 for spraying the crockery to be washed in a known manner. The bottom of washing tank 12 houses a fine-mesh filter 24 disposed in the path of flow of

The present invention relates to a dishwasher comprising a circulating pump, a washing tank provided with a substantially horizontal filter disposed in the path of water flow drawn by the circulating pump and rotating spray means capable of directing downwardly at least one water jet.

It is well known that the water jet directed downward be used mainly for cleaning automatically the above filter and any other coarse filter eventually associated to such horizontal filter. Another possible function of such water jet is to drive the rotation of the spray arm, even if for such function other water jets may be used. With the very efficient spray systems of modern dishwashers the speed of water jets is very high. If this is good for the water jets directed towards the crockery to be washed, it makes problem in its impingement against the fine-mesh horizontal filter placed below the spray arm, since such impingement creates many air bubbles which are driven in the chamber below the filter and sucked by the circulating pump. The presence of air bubbles in the water flow drawn by the circulating pump makes the working of this latter very unstable, since the rotational speed of the impeller can have quick increase and subsequent quick decrease. In order to avoid such unstable working (with consequent damages to the electric motor), it is known to have a high water level in the chamber so that the air bubbles have sufficient time to reach the surface without being sucked by the pump. This of course requires a higher amount of water per fill, which is not desirable in view of detergent concentration, impact on environment and energy needed for water heating.

A solution is disclosed by GB 2200834 in which a screen is disposed between the spray arm and the substantially horizontal filter for intercepting the water jet above such filter. This solution has the drawback of requiring an additional component of the dishwashing machine, with higher overall cost and an uneasy removal of the spray arm and the filter for cleaning thereof. Moreover the interception of the downwardly directed water flow totally prevents the cleaning action on the fine-mesh filter.

In accordance with the invention there is provided a dishwasher in which the substantially horizontal filter presents a not uniform percentage of open area. Preferably an area of the filter below a circular pattern of the downwardly

by parallel straight lines, is the cheapest one in term of mass production, bearing in mind that the filters 24 are obtained starting from a coil of thin stainless steel foil which is then subjected to an automatic forming and punching process. The higher percentage of open area in the side zones B gives a higher water flow rate which allows water flow even when the rest of the screen is soiled, so that the system is able to handle more soil.

According to a second embodiment of the invention (figure 4), the filter 24 is obtained through an injection-moulding process of a polymeric material. In this case the pitch of the holes of the filter 24 can be maintained constant on most of the surface thereof, and a circular zone 32 is provided (corresponding to the circular pattern P of the jet of water 30) with no holes, so as to avoid the entrapment of air in the water entering the chamber 18 but maintaining a cleaning cross action of the filter 24.

the water which, after having sprayed over the crockery, is collected in the chamber 18 and is drawn in again by the circulating pump 20. The filter 24 is substantially flat and, in its working configuration, substantially horizontal. It is provided with a circular aperture 24a in which a pump-protecting cylindrical filter assembly 26 is removably disposed, such assembly being disposed in the path of flow of the water which is drawn in by a discharge pump 28 from the chamber 18. The cylindrical filter assembly comprises a wide-mesh basket 26a inserted in a microfilter casing 26b. Such two components of the assembly 26 can be easily removed from each other so that the user can clean them.

Provided on the underneath side of the arm 22 is a nozzle 28 for directing a jet of water 30 downwardly. The jet of water 30 rotates with the arm 22 and, during its rotary movement, strikes the fine-mesh horizontal filter 24 along a circular pattern P (shown in dotted line in figures 3 and 4) and, intermittently, it strikes also the filter assembly 26 for providing an automatic cleaning thereof.

According to a first embodiment of the invention (figure 3), the fine-mesh filter 24 is made of punched stainless steel foil and presents a central zone A, in which the aperture 24a for the cylindrical filter assembly 26 is provided, and two side zones B, outside the circular pattern P of the jet of water 30. The zones A and B differ from each other in the percentage of open area. The central zone A presents holes having a diameter of 0,7 – 0,9 mm, preferably 0,8 mm, with a pitch so that the percentage of open area is in the range of 8% to 20%, preferably 13% to 18% (a simplified view of the punched area of zone A is shown in figure 6). The side zones B present holes having the same diameter of the zone A, but with a lower pitch (figure 5) so that the percentage of open area is in the range 20%-40%, preferably 27%-35%. Of course the same difference in percentage of open area may be obtained also by changing not only the pitch but also the diameter of the holes in the different zones. Moreover, instead of having three zones divided by straight lines as shown in figure 3, it would be possible to have a circular zone, in which the circular pattern P is included, in which the holes of the filter 24 have a pitch pattern similar to figure 6. However, the solution shown in figure 3, in which only the pitch of the holes changes and in which the three zones are divided

CLAIMS

1. A dishwasher comprising a circulating pump (20), a washing tank (12) provided with a substantially horizontal filter (24) disposed in the path of the flow of water drawn in by the circulating pump (20), and spray means (22, 28) capable of directing downwardly at least one rotating water jet (30), characterised in that such filter (24) presents a not uniform percentage of open area.
2. A dishwasher according to claim 1, characterised in that an area (A, 32) of the filter (24) below a circular pattern (P) of the downwardly directed jet (30) presents said percentage of open area lower than the other portions (B) of the filter.
3. A dishwasher according to claim 2, in which said filter (24) is a perforated or punched plate, characterised in that it presents one central zone (A) and two side zones (B) outside the circular pattern (P) of the downwardly directed jet (30), such two side zones (B) having a percentage of open area higher than the percentage of open area of the central zone (A).
4. A dishwasher according to claim 3, characterised in that said two side zones (B) have a plurality of holes with a pitch lower than the pitch of holes in the central zone (A) of the filter (24).
5. A dishwasher according to claim 3 or 4, characterised in that said two side zones (B) of the filter (24) present a percentage of open area comprised between 20% and 40%, preferably between 27% and 35%, while the central zone (A) of the filter (24) presents a percentage of open area comprised between 8% and 20%, preferably between 13% and 18%.
6. A dishwasher according to claim 5, characterised in that the holes of the filter (24) have a diameter comprised between 0,7 and 0,9 mm.
7. A dishwasher according to claim 2, characterised in that the filter (24) presents a substantially circular zone (32), corresponding to the circular pattern (P) of the downwardly directed jet (30), with no hole or perforation.






THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

Title: "Dishwasher"**Abstract**

A dishwasher comprises a circulating pump, a washing tank provided with a substantially horizontal fine-mesh filter (24) disposed in the path of the flow of water drawn in by the circulating pump, and spray means (22) capable of directing downwardly at least one rotating water jet for filter cleaning purposes. Such fine-mesh filter (24) presents an area below a circular pattern of the downwardly directed jet having a percentage of open area lower than the other portions (B) of the filter.

(fig. 1)






Fig. 1